DESCRIPTION OF REVISION APPROVED ECN NO. This document contains proprietary information and such informationmay not be disclosed to others for any purposes, Initial Release 16/6/15 16/6/15 T.Shihua not used for sales/marketing/procurement purposes without written permission 1 Electrical 1.1 Impedence 50₽ 0~11GHz 1.2 Frequency 1.3 Dielectric withstanding voltage 1500V(volts RMS) 32.8 1.4 Center contact resistance ≤ 1.5MΩ 1.5 Outer contact resistance $\leq 0.2 M\Omega$ 1.6 Insulation resistance: ≥5000MΩ 1/16-28UNEF-2A 5/8-24UNEF-2A 2 Environmental&Mechanical 2.1 Temperature range -55°~155°C 2.2 RoHs Compliant 2.3 Durability >500 cycles 3 Materials&plating 3.1 Body: Brass, nickel plated 3.2 Insulator: Teflon 3,3 Contact Pin: Bronze, Gold plated TITLE: DRAWN: T.Shihua 16/6/15 N/TNC-KK ENGINEER: C.Tao 16/6/15 www.rf-connector-china.com Notes: APPROVED: W.Qiang 16/6/15 N Female to TNC female adaptor 1.ALL SPECIFICATIONS ARE SUBJECT TO CHANGE NOTICE AT ANY TIME TOLERANCES UNLESS OTHERWISE SPEFICIED DIMENSION IN MILLIMETERS (mm) ±0.50 2.CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY ±0.10 PART NO: TRL-ZJQ-328909 SHEET: 1/1 N/A ANGLES ±1°

3