



1. 电气性能:

1. 特性阻抗: 50 Ω
1. 频率: DC~2GHz
2. 中心导体接触电阻: 1.5 MΩ max
3. 外导体接触电阻: 1 MΩ max
4. 介质耐压: 1500V
5. 绝缘电阻: 5000MΩ min

2. 材料&涂覆

1. 中心导体: 黄铜镀金 (48小时金)
2. 外壳: 黄铜镀镍 3μm
3. 绝缘材料: PTFE

3. 包装

1. 包装: 1pc/袋
2. 外箱: 瓦楞纸箱, 外贴包装内容

| | | | | | |
|------------------------|-------------|-----------|----------------------|-------|---|
| FIRST ANGLE PROJECTION | | SCALE | BNC-KHD | UNITS | UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE mm, TOLERANCES ARE: |
| THIRD ANGLE PROJECTION | | N/A | | mm | |
| | NAME | DATE | RF Coaxial Connector | REV | FRACTIONS DECIMALS ANGLES |
| DRAWN | Tomson Tang | 24-Feb-16 | | V1.0 | .X± .20± 1° .XX± .10 .XXX± |
| CHECKED | Mike Wang | 24-Feb-16 | | | |
| APPROVED | Teresa Ma | 24-Feb-16 | | | |

