


This document contains proprietary information and such information may not be disclosed to others for any purposes, nor used for sales/marketing/procurement purposes without written permission.  
 本文件包含专有信息，没有书面许可，该信息不能以任何形式披露给第三方，也不能用于任何目的的买卖，销售及采购。




1 Electrical Data

- 1.1 Impedance: 50 Ω
- 1.2 Working voltage: 335V(rms)
- 1.3 Frequency Range: 0-6GHz
- 1.4 Insulation resistance: 5000M Ω min
- 1.5 Dielectric strength: 1000V
- 1.6 Center contact resistance: 3M Ω max
- 1.7 Outer contact resistance: 2.5M Ω max
- 1.8 VSWR: 1.2:1

2 Material&Finish

- 2.1 Inner Contact: gold plated over Beryllium-copper.
- 2.2 Outer Contact: gold plated over brass.
- 2.3 Insulators: Teflon



Scale

1:1

Name Date

Designed Michael Tang 17-Aug-10

Checked Jason Cai 17-Aug-10

Approved Teresa 17-Aug-10

SMA-KHDC3  
 SMA Female for PCB  
 Edge

UNLESS OTHERWISE SPECIFIED  
 DIMENSIONS ARE mm, TOLERANCES ARE:  
 FRACTIONS DECIMALS ANGLES  
 .X ± .15 ±1°  
 .XX ± .05  
 .XXX ±

